

DS200 Series PRESSURE SENSOR

Three-in-One PRESSURE SENSOR Transmitter, Switch & Display

- Pressure Ranges 100mbar to 600bar
- Gauge or Absolute Versions
- Sealed to IP65 (Plug & Socket) or IP67 (M12 x 1 Thread or Cable)
- 4-digit LED rotating display
- 1 or 2 freely configurable switchpoints
- 4-20mA or 0-10VDC outputs
- Excellent Performance/Price Ratio

Options Available

Interim Pressure Ranges (Consult Factory)

Intrinsically Safe version: II (1) 2 G EEx ia IIC T4 (Zone 0/1)

Various mechanical connections including: G $\frac{1}{4}$, G $\frac{1}{2}$, G $\frac{3}{2}$ flush, $\frac{1}{4}$ "NPT & $\frac{1}{2}$ "NPT - all male

5-Pin M12x1 male connector (IP67), cable gland with 2m cable (IP67)

or Hirschmann DIN43650 Plug & Socket (IP65)

Improved accuracy (NL&H) - $\pm 0.125\%$ or $\pm 0.175\%$ /span BFSL

DESCRIPTION

The DS200 series of pressure sensors offers an integrated combination of pressure transmitter/transducer, intelligent pressure switch and digital display, along with a variety of pressure connection options, making it ideal for a wide range of applications including pharmaceutical, foodstuffs, pneumatics and hydraulics.

The digital display offers rotation on 2 axes, 240° on the front face and 300° from on the transducer housing axis, thus enabling adjustment to its optimum viewing position.

Configuration of the set-point(s) is via two buttons situated on the front of the display. Each point is freely configurable from 0% to 100% of full scale.

All units utilise a Stainless Steel diaphragm, ensuring compatibility with a wide range of process media and excellent long-term stability.

The DS200 can be supplied calibrated with additional instrumentation such as external displays or dataloggers if required, offering a single source solution for your system requirements.



DS200 Series PRESSURE SENSOR SPECIFICATION



CHARACTERISTICS	DS200	DS200V	UNITS
Pressure Ranges:	0.10 to 600	0.10 to 600	bar (Gauge or Absolute)
Safe Overpressure:	150	150	%Pressure Range
Supply Voltage:	18-41	19-30	Volts DC
Current Consumption:	<25	<15	MA
Load Driving Capacity:	1150	<1Meg	Ohms at Max. Supply Voltage
Output Current Zero Pressure:	4mA	0V	
Max. Pressure:	20mA	10V	
Electrical Connections	M12 x 1 male 5-pin connector (IP67 rated) as standard DIN43650 (1 set-point only) IP67 cable gland with 2m cable	M12 x 1 male 5-pin connector (IP67 rated) as standard IP67 cable gland with 2m cable	
Accuracy:	<0.25 (0.125 opt. >0.4bar)	<0.25 (0.125 opt. >0.4bar)	±%Pressure Range
Temp. Range (media) Operating:	-25 to +125	-25 to +125	°C
Compensated:	0 to +70	0 to +70	°C
Temperature Effect On Output:	<1	<1	±%Pressure Range over 0-70°C
Storage Temperature Range:	-40 to +85	-40 to +85	°C
Environmental Protection:	IP67 (IP65 with plug & socket)	IP67 (IP65 with plug & socket)	
Weight	200 (not including cable)	200 (not including cable)	Grams
Wetted Parts:	Stainless Steel & Viton	Stainless Steel & Viton	
Display:	4-digits, -1999 to +9999	4-digit, -1999 to +9999	
Set Points:	PNP type, max rating 125mA	PNP type, max. Rating 125mA	

All dimensions in mm

